WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

A

(11) International Publication Number:

WO 92/04062

A61M 5/158, 5/32

A1

(43) International Publication Date:

19 March 1992 (19.03.92)

(21) International Application Number:

PCT/NO91/00104

(22) International Filing Date:

24 July 1991 (24.07.91)

(30) Priority data:

903910

7 September 1990 (07.09.90) NO

(71) Applicant (for all designated States except US): PREISS, Otto, T. [NO/NO]; Svartdalsveien 29, N-0393 Oslo 3 (NO).

(71)(72) Applicant and Inventor: HEIMREID, Bent [NO/NO]; Junoveien 19, N-3942 Skjelsvik (NO).


(74) Agent: HELGERUD, Jan; Bryns Patentkontor A/S, P.O. Box 9566, Egertorget, N-0128 Oslo 1 (NO).

(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CI (OAPI patent), CM (OAPI patent), DE, DE (European patent), DK, DK (European patent), ES, ES (European patent), FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL, NL (European patent), NO, PL, RO, SD, SE, SE (European patent), SN (OAPI patent), SU+,TD (OAPI patent), TG (OAPI patent), US.

Published

With international search report. With amended claims.

(54) Title: A CANNULA



(57) Abstract

An intravenous cannula (1) with a bevelled point (2) is designed so as to make the cutting edge (3) of point (2) extend along the portion of the cannula (1) wall which is intended to lie furthest away from the skin (8) in use. The cutting edge (3) is preferably placed along the light opening (6) of cannula (5).

+ DESIGNATIONS OF "SU"

Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

appn	cations under the PC1.				
AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinça	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CC	Congo	KP	Democratic People's Republic	SE	Sweden
CH	Switzerland		of Korea	SN	Senegal
CI	Côte d'Ivoire	KR	Republic of Korea	su+	Soviet Union
СМ	Cameroon	LI	Lechtenstein	TD	Chad
cs	Czechoslovakia	LK	Sri Lanka	TC	Togo
DE	Germany	LU	Luxembourg	us	United States of America
DK	Denmark	MC	Monaco	,	

A cannula.

The present invention relates to a cannula, preferably an intravenous cannula of the kind that has a bevelled point forming a cutting edge.

At present, there is a veriety of cannulae on the market, however, they only differ in details as regards connection with tubing, medicament wells, and the like.

It is common to all these cannulae that the cutting edge of the cannula is provided along a portion of the cannula circumference and, also, along the portion of the cannula circumference which is intended to lie closest to the skin when in use.

With correct use and correct equipment complications will generally be avoided when, especially peripheral venes are punctured and cannulated, however, some cases of complications or accidents will be unavoidable.

If the cannula is inserted into the vene in a too steep or vigorous manner, there is a hazard of the opposite vene wall being punctured as well. Such a puncture may, in turn, cause blood to ooze from the vene to the tissue with a consequent haematoma.

Also, medicaments may be injected into areas outside the vene in stead of into the blood stream, because the introduced plastic tube is provided adjacent to the unintended place of puncture. Furthermore, the inserted plastic tube may unintentionally be perforated by unintended movement of the cannula in the tube in connection with removal.

Among known technology, we refer to EP 0 238 419 A3 and EP 0 271 775 A3, DE-OS 24 34 618, GP-PS 1 298 707, and US-PS

20

35

2 748 769.

All cited documents disclose straight cannulae or cannulae which are slightly arched at the point, with the cutting edge of the cannula extending along the periphery of the cannula tube, and with the cannula, additionally, being equipped with auxiliary openings or with a two-piece cannula opening, this to provide a certain turbulence when injecting.

There are also cannulae on the market the cutting edge of which is displaced by grinding to a point between the periphery and the light opening.

It is an object of the present invention to improve known technology, and the invention, thus, relates to a cannula with a bevelled point which forms a cutting edge, and the cannula is characterized by the fact that the cutting edge of the point extends along the light opening of the cannula in the portion which is placed furthest from the skin when the cannula is inserted.

Experiments proved that the cannula according to the invention results in a smaller penetration or wound area than known cannulae.

This was confimed in tests on patients, up to 90% of whom said on inquiry that piercing with the cannula according to the invention caused less discomfort than piercing with cannulae of known technology. The tests were made with masked cannulae, one of each kind and one on each arm of the same patient.

Another advantage which is achieved with the cannula according to the invention is that the cannula opening will face the stream when inserted into the vene, which will provide a more rapid "backflow" and, thus, confirmation that the cannula is in place.

Other advantages of the invention will appear from the following disclosure with reference to the accompanying drawings, in which:

- 5 Figure 1 shows a conventional cannula with a cannula tube 1 and a point 2;
 - Figure 2 shows an enlarged portion of the point area of Figure 1;
- Figure 3 shows a conventional cannula in a position for penetration;
- Figure 4 shows the situation in case of unintentional penetration of the opposite vene wall;
 - Figure 5 shows the unintended situation occurring when the cannula tube is wrongly placed;
- Figure 6 shows an unintentional perforation of the cannula tube by the pont of the cannula;
 - Figure 7 shows the general position of the point of the cannula according to the invention (compare with Figure 2);
 - Figure 8 corresponds to Figure 3, but shows the invention;
- Figure 9 basically corresponds to Figure 4, but shows the advantage achieved by the invention;
 - Figure 10 and

25

Figure 11 show a preferred embodiment of the invention (compare with Figure 7);

10

15

25

30

4

Figure 12 shows the preferred embodiment and corresponds to Figure 9;

Figure 13 shows the preferred embodiment and corresponds to Figure 6;

As mentioned above all cannulae on the market at present are of the kind as shown in Figure 1, designed as shown in Figure 2 with the edge of the point being provided in the part of the cannula wall that is intended to lie in contact with the skin when used.

This is diagrammatically shown in Figure 2, and the accidents that may occur when the cannula is used are illustrated in Figures 3 - 6.

In Figure 3 cannula 1 with point area 2 and the associated plastic tube 7 is positioned to penetrate the skin 8 and vene 9 by also piercing one vene wall 9b.

Figure 4 shows what may happen if the cannula is inserted too steeply or forcefully. The opposite vene wall 9c is puctured, which will cause a hazard of blood oozing out of the vene with a consequent haematoma. The patient, thus, must be pierced once more.

In use, blood and medicament may then coze out of opening 9c, so that there is also an accumulation of liquid outside the vene with further hazard of injuries to tissue and necrosis, see Figure 5.

Figure 6 shows a situation which may occur due to the fact that the point of the cannula is moved inside the cannula tube, the latter may be punctured at 7a.

As mentioned above, it is an object of the invention to remedy the shortcomings of known technology, and according to the general design of the invention this is achieved by

20

30

placing the cutting edge 3 of the cannula point 2 along the portion of the cannula wall which is intended to face away from the skin in use.

Generally, the cutting edge is achieved by simple angular cutting of the cannula, however it is possible both on conventional cannulae and on cannulae according to the invention to sharpen the cutting cannula edge, as indicated in Figure 2, so as to provide a regular point 4 in stead of the present oval arch.

The cannula according to the inventinn is illustrated in Figures 8 and 9 with Figure 8 corresponding to Figure 3 immediately before the skin is punctured.

In Figure 9 the situation shown is immediately after cannula 1 with plastic tube 7 has penetrated the skin 8 and one vene wall 9a. It will appear that by placing the cutting edge according to the invention a more flat "underside" of the point area 2 is achieved, which will substantially reduce the hazard of puncturing the other vene wall 9b, as shown in Figure 4.

The embodiment shown in Figures 7 - 9 represents an essential improvement as compared to known technology, as illustrated in Figures 3 - 6.

There is, however, a certain though strongly reduced hazard of unintentional penetration of a vene wall upon insertion of the cannula, also in connection with the object of the present invention. This is shown directly in Figure 4, but even after successful insertion a puncture may occur on the side where the point of the cannula is placed.

The preferred embodiment of the invention, as mentioned above, should solve this problem too, and this is the case with the embodiment generally shown in Figure 10.

10

15

It is achieved by reshaping the point area 2 to move the cutting edge 3 of the cannula from the outer diameter to the inner diameter or light opening, indicated by numeral 6 in Figures 7 and 10.

By moving the cutting edge 3 the hazard of unintentionally puncturing the vene wall is substantially reduced, as there is provided a further surface 11 as will appear, e.g. from Figure 12. Said surface may slide against the vene wall preventing the point from getting caught in the vene wall and unintentionally puncturing the wall.

According to the invention as disclosed above a cannula is achieved in a simple and inexpensive manner, and safety in operation and use is enhanced without sacrificing the safety of known cannulae and, additionally, without causing essentially increased costs.

The invention, thus, represents an essential improvement as regards operation and use of cannulae in connection with puncturing and cannulation of venes.

25

30

35


PATENT CLAIM:


A cannula (1) with a bevelled point (2) which forms a cutting edge (3), characterized in that the cutting edge of point (2) extends along the portion of the light opening (6) of the cannula which, in use, is intended to be placed furthest away from the skin (8).


AMENDED CLAIMS


[received by the International Bureau on 6 February 1992 (06.02.92); original claim 1 replaced by amended claim 1 (1 page)]


Cannula (1) with a bevelled point (2) which forms a cutting edge (3), characterized in that the cutting edge (3) of the point (2) extends along the portion of the light opening (6) of the canula (1) which, before the penetration of the skin (8), is furthest away from the skin (8).















SUBSTITUTE SHEET





SUBSTITUTE SHEET





SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International Application No PCT/NO 91/00104

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all)							
According to International Patent Classification (IPC) or to both National Classification and IPC IPC5: A 61 M 5/158, 5/32							
II. FIELDS SEARCHED							
		Minimum Docume	ntation Searched'				
Classification							
IPC5		A 61 M					
	Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in Fields Searched ⁸						
SE,DK,F	I,NO	classes as above					
III. DOCUI	MENTS (CONSIDERED TO BE RELEVANT ⁹					
Category *		tion of Document,11 with indication, where app	propriate, of the relevant passages ¹²	Relevant to Claim No.13			
Х		, 1298707 (SIEMENS AKTIENG		1			
l^	6	December 1972, see page 2	. line 66 -	-			
		ine 101; figures 1-2	•				
			1001	7			
Х	DE, C	1, 346472 (METZ) 31 Decembe	r 1921, E2.	1			
	5	ee page 1, line 43 - line igures 1-3	33,				
	•						
x l	US, A	, 2524713 (N.P. PLECHAS) 3	October 1950,	1			
		ee figure 1					
l., l		4200720 (SUADDOCK) 10 1-		1			
Х		, 4368730 (SHARROCK) 18 Ja ee figure 7	nuary 1965,	•			
* Special categories of cited documents: 10 A document defining the general state of the art which is not considered to be of particular relevance T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention							
re earlier document but published on or after the international filing date 'E' earlier document of particular relevance, the claimed invention cannot be considered to							
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another systems of particular relevance, the claimed invention							
citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "O" document referring to an oral disclosure, use, exhibition or other means "O" document referring to an oral disclosure, use, exhibition or other means "O" document referring to an oral disclosure, use, exhibition or other means							
"P" docu late							
IV. CERTIFICATION							
29th November 1991 Date of the Actual Completion of the International Search 1991 -12- 0 6							
Internationa							
	1						
	CITE	DISH PATENT OFFICE	Folke Svensson	ائر ا			
or PCTUC	<u> </u>	DISH [VICH OI] IOF	1011/2 072/10001				

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)					
ategory *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No			
(US, A, 4642101 (KROLIKOWSKI ET AL) 10 February 1987, see column 2, line 60 - column 3, line 3; figures 3-5	1			
•	SE, C, 135689 (AKTIEBOLAGET STILLE-WERNER) 13 May 1952, see page 2, column 1, line 30 - line 50; figure 3	1			
-	DE, A, 2005519 (ROESCHEISEN & CO SUDDEUTSCHE BINDENFABRIK) 28 October 1971, see page 10, line 5 - page 11, line 16; figures 1-2	1			
	US, A, 2187259 (G. E. BARNHART) 16 January 1940, see page 2, column 2, line 24 - line 28; figure 3	1			
	US, A, 2601580 (B.J. YANUS) 24 June 1952, see column 1, line 52 - column 2, line 4; figures 1,4-5	1			
	US, A, 4808170 (THORNTON ET AL) 28 February 1989, see column 3, line 10 - line 28; figures 4-5	1			
	A/210 (extra sheet) (January 1985)				

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.PCT/NO 91/00104

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on 31/10/91 The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report		Publication date	Patent family member(s)		Publication date	
GB-A-	1298707	72-12-06	CH-A- DE-A-B-C FR-A-	501410 1927868 2048823	71-01-15 70-12-03 71-03-19	
DE-C-	346472	21-12-31	NONE			
US-A-	2524713	50-10-03	NONE			
US-A-	4368730	83-01-18	NONE			
US-A-	4642101	87-02-10	NONE			
SE-C-	135689	52-05-13	NONE			
DE-A-	2005519	71-10-28	NONE		·	
US-A-	2187259	40-01-16	NONE			
US-A-	2601580	52-06-24	NONE		-	
US-A-	4808170	89-02-28	NONE			